

ZEEKR 7X Australia

Tyre and rim specifications

All wheels use the lug/stud pattern: 5x108 PCD (Pitch Circle Diameter)

Centre Bore: 63.4mm

Lug/Bolt/Thread/Pitch: M14x1.5

(Hex: 19mm) (Thread/Shank Length: 30mm) (Radius: Ball) (Seat Type: 60 Degree Conical)

ET: +44mm (Wheel Offset)

255/50 R19

Tyre designation:	255/50 R19
Rim size and profile:	8.0J x 19
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	44
Front wheel track (mm):	1649
Rear wheel track (mm):	1654

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
G0027E1RE8125B75B2RY	Std Front and Rear (SB)
G0027E1RE8125EA0B2RY	Std Front and Rear (SB)

265/45R20

Tyre designation:	265/45R20
Rim size and profile:	9.0J x 20
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	44
Front wheel track (mm):	1649
Rear wheel track (mm):	1654

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
G0027E1AE9075EA0B2RY	Std Front and Rear (SB)
G0027E1RE8125EA0B2RY	Opt Front and Rear (OB)

265/40R21

Tyre designation:	265/40R21
Rim size and profile:	9.0J x 21
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	44
Front wheel track (mm):	1649
Rear wheel track (mm):	1654

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
G0027E1AE9075EA0B2RY	Opt Front and Rear (OB)